

DIAMOND Intercom and Radio Combiner System



Drumgrange has developed a digital intercom and radio combiner system for use on land and maritime platforms. An ideal solution for patrol craft and vehicles, Diamond provides voice connectivity between multiple users and on-board radios and also integrates engine & system alarms to ensure platform and crew safety.

Driven by the toughest user requirements in the harshest of environments, the Diamond system balances intuitive functionality and ease of use with a robust, low-maintenance design. In the most challenging situations, crew members can be confident of independent access to both secure and non-secure communications, uninterrupted intercom facilities and voice-activated comms.

Diamond's modular design and intuitive interface allows for rapid fault finding and module replacement with no need for complicated and expensive diagnostic equipment.

Key Features

- Designed for single hand operation under high-speed transit
- User-specific VOX sensitivity control. User can personalise voice-activated comms at any time
- Designed to Def Stan 00 35 Environmental Requirements
- Designed to Def Stan 59-41 I and EN60945:2002 ACI:2008 EMC
- Can accommodate up to 8 users and 6 radios with an additional 2 configurable digital outputs
- Clear, reliable communications
- Simple operation/Compact footprint/Lightweight/Low power/Fast, easy maintenance
- Fully isolated for secure and non-secure operation
- Headset agnostic through the use of smart cables
- 8 user-defined audible alarm inputs e.g. engine alarm, engine temperature and low battery warnings



Technical Specification

General	
Audio Interfaces and Processing:	High quality, digital audio (300Hz – 8kHz). User-controllable VOX function.
Power:	9 - 32 VDC, Max 1500mA @ 12V
Weight (ea):	Hub: 2.5kg User Node: 0.7kg
Size (W x H x D):	Hub: 220mm x 160mm x 89mm User Node: 100mm x 120mm x 40mm

STORAGE / OPERATING ENVIRONMENT	
High Temperature:	Storage: 70°C Operating: 55°C
Low Temperature:	Storage: -34°C Operating: -25°C
Sealing	IP66 / IP67 Protected against dust, powerful water jets and temporary immersion in water Tested in accordance with DEF-STAN 00-35 Part 3, Issue 4, Test CL25, Blowing Dust and Blowing Sand 3 CL5.
Random Vibration:	Tested in accordance with DEF STAN 00-35, Issue 3, Part 3, Test M1 Annex A, Figure A26 + A27 - Light Vehicle - Material on Sponson or Installed in Hull, Tracked Vehicle - High Level Test (Vertical Level Only) Annex A, Figure A29 - Material Deployed in Ships Smaller than Mine Sweepers
Shock	Tested in accordance with DEF-STAN 00-35 Part 3, Issue 4, Test M3, Table 1

Interfacing	
Headset interface:	Flexible headset options for different microphones and sensitivities Monaural or binaural options.
Radio interface:	Flexible radio input/output allows use of any radio. Fully isolated analogue output to radio audio and PTT lines.
Alarm interface:	8 user-definable audible alarms (spoken, tonal, etc.).

User Controls	
Control Subsets on User Node:	Radio Selection Volume(Min/Max) VOX Sensitivity (PTT/Open) Push-To-Talk button (Selected Radio) Push-To-Talk button (Intercom) Illumination activation button to check radio selection
Radio TX Inhibit.	Single switch places system in radio "listen only" mode.

Contains public sector information licensed under the Open Government Licence v3.0.

Drumgrange Limited
Unit A, The Forum, Hanworth Lane,
Chertsey, Surrey, KT16 9JX
+44 (0)1932 581100
Email: info@drumgrange.com
www.drumgrange.com



013

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001 • TickITplus

